

## **PowerMaster-10 G2** PowerG-based Ultra-compact Wireless Alarm System

### **Features that Make** a Difference:

- Unmatched affordability and performance
- Accommodates over 120 wireless devices:
  - Up to 30 zones
  - Up to 8 keypads, 8 keyfobs, 2 sirens, 4 repeaters
- Optional GSM/GPRS and IP internal modules
- Extensive range of PowerG peripherals for every application
- Remote configuration and diagnostics with system status indications
- All devices are configured from the panel
- SirenNet Leverages smoke detector buzzers for all alarms

### **A New Era in Intrusion Alarm Systems**

PowerMaster-10 G2 is an ultra-compact, wireless alarm system suitable for advanced applications and heavy duty operations. It has a superior range, prolonged battery life and unmatched wireless robustness. Moreover, it provides outstanding full two-way wireless functionality with all peripherals.

Using Visonic's revolutionary PowerG network technology, PowerMaster-10 G2 fully answers the most demanding requirements facing the security industry today, as well as the challenges of tomorrow.

#### **PowerG Robustness** and Reliability

I Visonic

43 PP 010K

0 3 6

04

[A]

7 8 1 9 \* 0 0 8 m #

+0

- Frequency Hopping Spread Spectrum (FHSS).
- Full two-way synchronized TDMA wireless network - Provides streamlined communication and improved channel efficiency.
- Huge transmission range of 2000m (6500ft) line of sight\* - Covers significantly larger premises than traditional systems, without repeaters.
- Highly secured AES-128 encrypted wireless communication -Surpasses the most demanding industry standards.
- Adaptive transmission power Saves energy and significantly extends battery life.



\*Measured line-of-sight transmission range: 2000m (6500ft) at 8m (24ft), 750m (2500ft) at 2m (6.5ft)

www.visonic.com



# New Toolset for Faster and Easier Installation

- Special enrolment button on each device simplifies enrolment procedures.
- All devices are configured from the panel No hardware switches and no need to re-open the peripherals once closed.
- Customized configuration templates enable configuration of the devices collectively.
- Visible signal quality indication shown on the device

   Enables the installer to choose the optimal location without having to walk to the panel during mounting.
- Powerful diagnostic tool indicates RF link quality, based on the previous 24 hours' statistics and on-demand bi-directional measurements, displaying immediate problems and enabling verification of the installation during house setup.

### Powerful Tools for Central Monitoring Stations

- Remote enrolment, configuration and review of all peripherals in the system.
- Initiate remote walk test with assistance from anyone in the house.
- Remote diagnostics of wireless connection and RF link quality for all peripherals – Based on the previous 24 hours' statistics and on-demand bi-directional measurements.

### Green, Energy-saving System

- Two-way, synchronized, spread spectrum communication eliminates unnecessary re-transmissions.
- Typical 5-8 years' battery life for all peripherals.
- Minimum power consumption and pollution due to adaptive transmission power that is determined according to the distance from the panel and level of RF interference.

### **Specifications**

RF network PowerG - Frequency hopping multi-channel (CDMA)		
Frequency bands (Mhz) 433 – 434	868 - 869	912 - 919
Hopping frequencies 8	4	50
Encryption		AES-128
Number of zones		
User codes		
Back-up battery12 hour back-up – 4.8V, 1300mAh, NiMH 24 hour back-up – 4.8V, 2200mAh, NiMH		
Dimensions		80 x 55mm 32 x 7 x 2in)
Weight	6	58kg (23oz)
Power supply Internal or external according to local regulations		
Reporting formats Analog: SIA, Contact ID, Scancom; IP: SIA IP, Visonic PowerNet		
Communication	PSTN, GSN	1, GPRS, IP

### www.visonic.com

Contact Visonic for further information: Email: info@visonic.com Tel: +972 3 6456789

Product offerings and specifications are subject to change without notice. Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative. © 2012 Tyco International Ltd. and its respective companies. All rights reserved. POWERMASTER-10 DATA SHEET ENG C-800748 (Rev.02)